



IRONWOLF PRO

NAS



3.5 HDD DATA SHEET

The Power of Agility for Creative Pro and SME NAS Enclosures



IronWolf™ Pro is designed for everything business NAS. Get used to tough, ready and scalable 24x7 performance that can handle multi-drive environments with a wide range of capacities.



Best-Fit Applications

- 1- to 16-bay business network attached storage (NAS)
- Backup, archiving and disaster recovery
- On-premise private cloud
- Virtual storage



Key Advantages

Optimized for NAS with AgileArray.™ AgileArray is built for dual-plane balancing and RAID optimization in multi-bay environments with the most advanced power management possible.

High performance means reduced lag times or downtime for users during high traffic time for the NAS. Seagate leads the competition with the highest performance in NAS-class drives.¹

Actively protect your NAS with IronWolf Health Management² focusing on prevention, intervention and recovery.

Seagate® Rescue Data Recovery.³ IronWolf Pro comes with extra peace of mind for any mechanical, accidental or natural disaster. With a 90% success rate of in-house recovery, Seagate has your back with a 2-year included Rescue Data Recovery plan.

Rotational Vibration (RV) mitigation. IronWolf Pro comes standard with RV sensors to maintain high performance in multi-bay NAS enclosures.

Range of capacities up to 10TB. More capacity options mean more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Do more in multi-user environments. IronWolf Pro provides a workload rate of 300TB/year. Multiple users can confidently upload and download data to the NAS server, knowing IronWolf Pro can handle the workload, whether you are a creative professional or a small business.

1.2M hours MTBF, 5-year limited warranty represents an improved total cost of ownership (TCO) over desktop drives with reduced maintenance costs.

Designed for always on, always accessible 24x7 performance. Access your data on your NAS any time, remotely or on site.

¹ Performance may vary depending on user's hardware configuration and operating system.

² Contact your Seagate sales representative for further information.

³ Registration required to activate. Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details.



Specifications	10TB ^{1,2}	8TB ^{1,2}	6TB ^{1,2}	4TB ^{1,2}	2TB ¹	
Standard Model Number	ST10000NE0004	ST8000NE0021	ST8000NE0004	ST6000NE0021	ST4000NE0025	ST2000NE0025
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features						
Drive Bays Supported	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays
Multi-User Technology (TB/yr)	300	300	300	300	300	300
IronWolf Health Management ³	Yes	Yes	Yes	Yes	Yes	No
Rotational Vibration (RV) Sensors	Yes	Yes	Yes	Yes	Yes	Yes
Hot-Plug Support ⁴	Yes	Yes	Yes	Yes	Yes	Yes
Cache (MB)	256MB	256MB	256MB	256MB	128MB	128MB
Reliability/Data Integrity						
Mean Time Between Failures (MTBF) (hours)	1.2M	1.2M	1.2M	1.2M	1.2M	1.2M
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%	0.73%	0.73%
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours (per year)	8760	8760	8760	8760	8760	8760
Sector Size (Bytes per Logical Sector)	512E	512E	512E	512E	512E	512
Rescue Services ⁵	Yes	Yes	Yes	Yes	Yes	Yes
Limited Warranty (years)	5	5	5	5	5	5
Performance						
Spindle Speed (RPM)	7200	7200	7200	7200	7200	7200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max Sustained Transfer Rate OD (MB/s)	214	214	214	214	214	195
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single	Single	Single
Rotational Vibration @ 10-1500 Hz (rad/s ²)	12.5	12.5	12.5	12.5	12.5	12.5
Power Consumption						
Startup Current, Typical (12V, A)	2.0	2.0	2.0	2.0	2.0	2.0
Idle Power, Average (W)	4.4	7.6	4.4	7.6	6.0	4.5
Average Operating Power (W)	6.8	9.0	6.8	9.0	6.7	7.5
Standby Mode, Typical (W)	0.8	0.6	0.8	0.6	0.6	0.8
Sleep Mode, Typical (W)	0.8	0.6	0.8	0.6	0.6	0.8
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
Environmental						
Temperature (°C)						
Operating (ambient, min)	5	5	5	5	5	5
Operating (drive case, max)	60	60	60	60	60	60
Nonoperating (ambient, min)	-40	-40	-40	-40	-40	-40
Nonoperating (ambient, max)	70	70	70	70	70	70
Vibration, Nonoperating: 10Hz to 500Hz (Grms)	2.27	5	2.27	5	5	5
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40	70/40	70/40	70/40
Shock, Nonoperating, 1ms and 2ms (Gs)	250	250	250	250	300	300
Physical						
Height (mm/in)	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028	26.11/1.028
Width (mm/in, max)	101.85/4.01	101.85/4.01	101.85/4.01	101.85/4.01	101.85/4.01	101.85/4.01
Depth (mm/in, max)	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787
Weight (g/lb, typical)	650/1.433	780/1.72	650/1.433	780/1.72	680/1.50	550/1.21

¹ One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

² Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

³ Only available on Synology NAS enclosures. Synology models may vary. Please contact your Seagate sales representative for further information.

⁴ Supports Hot-Plug operation per Serial ATA Revision 2.6 specification.

⁵ Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.

seagate.com



AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00